




# Tripods, levelling staffs and fasteners



## THE BASIS FOR RELIABLE WORK

To make full use of all the capabilities offered by a rotation laser or automatic level, a tripod is necessary. Laserliner offers an extensive range of tripods, since different tasks call for different technical solutions. Wallmounts ease ceiling work.



Professional crank lift on the professional crank tripod with mm graduation



Quick-release lock for equal extension of all legs



The seat for the instrument is milled and surface-ground



An all-round steel chain prevents the legs from spreading on smooth floors



Crank lift with mm graduation



Sturdy steel feet for secure positioning



Hook for plumb bob directly beneath the fixing screw




Adjustable carrying strap

Laser and levelling device accessories

**Compact Tripod 120 cm**



**High-quality mini crank tripod of aluminium**  
 – Suitable for use on different surfaces through special combination feet (rubber/steel top)  
 – 5/8" thread adapter



**ORDER NO. EAN-CODE PU**

080.29 4 021563 652266 1




**PT**

**Compact Tripod 300 cm**



**High-quality, very compact crank tripod made of aluminium**  
 – 5/8" thread adapter  
 – Circular vial  
 – Multi-section telescoping tripod legs and crank height adjustment permit large adjustment range.  
 – Special combination feet (rubber/steel tips) facilitate adaptation to different surfaces.



**ORDER NO. EAN-CODE PU**

080.37 4 021563 670666 1




**PT**

**Aluminium Lightweight Tripod 165 cm**



**Lightweight design with milled mounting surface**  
 – 5/8" thread adapter  
 – Sturdy steel feet  
 – Quick-release lock

**Not for ACL 2C, ACL 3C, ACL 4C, ACL 360°, ECL 8P, PCL 10**



**Inclusive:** hook for plumb bob, carrying strap

**ORDER NO. EAN-CODE PU**

080.00 4 011879 633967 1




**PT**

**Ball-head Tripod 165 cm**



**Lightweight design with ball shaped mounting surface**  
 – 5/8" thread adapter  
 – Sturdy steel feet  
 – Quick-release lock

**Special for automatic levels AL 22 / 26.**



**Inclusive:** hook for plumb bob, carrying strap

**ORDER NO. EAN-CODE PU**

080.06 4 021563 658190 1




**IQ**

**Aluminium Tripod 170 cm**



**Heavy design with milled mounting surface**  
 – 5/8" thread adapter  
 – Sturdy steel feet  
 – steel chains  
 – Quick-release lock

**Not for ACL 2C, ACL 3C, ACL 4C, ACL 360°, ECL 8P, PCL 10**



**Inclusive:** hook for plumb bob, carrying strap

**ORDER NO. EAN-CODE PU**

080.10 4 011879 630935 1



**IQ**




Laser and levelling device accessories

**Crank Tripod 160 cm**



- Design with crank height adjustment and quick-lock**
- 5/8" thread adapter
  - Circular vial
  - Sturdy steel feet
  - steel chains



**Inclusive:** hook for plumb bob, carrying strap

ORDER NO.	EAN-CODE	PU
080.30	4 011879 630959	1




**PT**

**Professional Crank Tripod 260 cm**



- Heavy design with integrated professional crank height adjustment**
- 5/8" thread adapter
  - Wide range of adjustment through extremely high lift
  - Crank can be fixed in place without any play.
  - Sturdy steel feet
  - steel chains



**Inclusive:** carrying strap

ORDER NO.	EAN-CODE	PU
080.33	4 021563 650637	1




**IQ**

**Professional Crank Tripod 300 cm**



- Heavy design with integrated professional crank height adjustment**
- 5/8" thread adapter
  - Extremely long crank lift allows a large range of adjustment
  - Crank lift can be fixed and adjusted without play
  - Special combination feet (rubber steel tips) facilitate adaptation to different surfaces.
  - Sturdy steel feet
  - steel chains



**Inclusive:** carrying strap

ORDER NO.	EAN-CODE	PU
080.34	4 021563 662296	1




**IQ**

**Professional Crank Tripod 320 cm**



- Super-robust design for outdoor areas**
- 5/8" thread adapter
  - Suitable for windy conditions thanks to stability fitting and double-acting quick release lock
  - Circular vial
  - Sturdy steel feet
  - Three-legged frame for maximum stability
  - Crank lift can be fixed and adjusted without play
  - Special combination feet (rubber steel tips) facilitate adaptation to different surfaces.



**Inclusive:** hook for plumb bob, carrying strap

ORDER NO.	EAN-CODE	PU
080.36	4 021563 663927	1



**IQ**

**Telescopic Stand 330 cm**



- High-quality aluminium telescopic stand, ideal for quick changes in applications where working positions vary**
- The stand is clamped between floor and ceiling then the laser measuring tool is turned manually to set it to the correct height ready for operation.
  - 5-piece design for easy transport
  - Height approx. 330 cm



**Inclusive:** telescopic adapter, softbag

ORDER NO.	EAN-CODE	PU
090.120A	4 021563 665372	1



**PT**

**SOFT**

**Telescopic adapter**



- Adapter for telescopic stand 330 cm**
- For retrofitting and multiple use of laser measuring instruments on telescopic stand.
  - With additional 1/4" thread

**For all laser measuring instruments**



ORDER NO.	EAN-CODE	PU
090.120.1	4 021563 661084	1



**PT**


Laser and levelling device accessories



MiniStand 1/4"



- Mini-tripod made of aluminium**
- for LRM pocket, SCL 2, SCL 3 etc.
  - 1/4" tripod connection
  - Ball joint
  - Telescoping tripod legs



ORDER NO.	EAN-CODE	PU
090.130A	4 021563 670550	1




PT

FlexPod



- Nylon thermoplastic mini stand for LRM Pocket, LRM Pocket Pro etc.**
- 1/4" tripod connection
  - Ball joint and clamping screw for stepless adjustment
  - With Velcro fastener for securing to shafts, extruded sections and roof laths
  - Tripod feet with non-slip rubber caps
  - Extendable



ORDER NO.	EAN-CODE	PU
090.131A	4 021563 677245	1




PT

FixPod 155 cm

NEW



- Tripod for SuperCross laser series and laser distance meter**
- 1/4" tripod connection
  - 3-way tripod head
  - Crank height adjustment and telescopic tripod legs
  - Rubber-steel tips for use on different surfaces



Inclusive: softbag

ORDER NO.	EAN-CODE	PU
090.132A	4 21563 678990	4



PT

