

Laser and levelling device accessories



A comprehensive assortment of levelling staffs to cover the most diverse of applications. Particularly well suited for measuring ground levels or interior/exterior measurements. Suitable for use with automatic levelling and laser measuring instruments.



Flexi Levelling Staff
red / green



For all measurement of floor height
 – Reference height approx. 80-190 cm ± 50 cm measurement range, max. length approx. 240 cm
 – Height difference can be read off directly with no calculation necessary
 – Unmatched by any normal levelling staff

Flexi levelling staff red
 – Ideal for red lasers

Flexi levelling staff green
 – Ideal for green lasers



	ORDER NO.	EAN-CODE	PU
red	080.50	4 011879 631147	1
green	080.51	4 021563 664948	1

PT

Flexi-Slider



Optimum positioning aid for laser receiver at Flexi levelling staff
 – Smooth slider for quick and easy use
 – With quick-action clamp



	ORDER NO.	EAN-CODE	PU
	080.52	4 021563 673292	1

IQ

Telescopic Levelling Staff



Easily legible, highly stable levelling staffs for use even under extreme conditions
 – Made of strong aluminium section
 – For optical levels and rotary lasers
 – Telescopic Levelling Staff 4 m: max. height 4 m, min. height 1.19 m
 – Telescopic Levelling Staff 5 m: max. height 5 m, min. height 1.22 m



	ORDER NO.	EAN-CODE	PU
	080.40	4 011879 630966	4 m
	080.41	4 011879 630973	5 m

PT