

# Geo3X HP

## Small but powerful




» **The ideal instrument for numerous alignment, measurement and levelling tasks. Projecting 3 high powered laser crosses at 90° to each other.**

- » · The versatile multi-functional mount offers a variety of mounting options to increase flexibility and productivity
- 3 laser crosses
- Compact, handy size
- Shock-resistant design suitable for robust use on construction sites
- Self-levelling function can be switched off for manual use

1 Keypad



TECHNICAL DATA	GEO3X HP	FEATURES	SUPPLIED WITH
			<b>ART.-NO. 520600</b>
Self-levelling range	± 3°	<ul style="list-style-type: none"> <li>· 2 laser crosses at 90° to each other</li> <li>· Laser cross to the ceiling</li> <li>· Individually selectable laser lines</li> <li>· Self-levelling function can be switched off for manual use</li> <li>· Visual and audible alarm when out of level</li> <li>· Multi-functional mount with               <ul style="list-style-type: none"> <li>· strong magnets on the back face</li> <li>· can be fixed to a wall</li> <li>· strap attachment</li> <li>· height adjustable</li> <li>· 1/4" and 5/8" tripod thread</li> </ul> </li> <li>· Pulse function for use with receiver (optional) to extend working range up to 60 m</li> <li>· 1/4" thread on the instruments base</li> </ul>	<ul style="list-style-type: none"> <li>· Multi-functional mount</li> <li>· 3 x AA Alkaline battery</li> <li>· Padded carrying bag</li> </ul>
Accuracy	± 3 mm / 10 m		
Working range without receiver	20 m*		
Working range with receiver (optional)	60 m		
Power supply	3 x AA Alkaline		
Operating time (all lines switched on)	12 h		
Dust/waterprotection	IP 54		
Laser diode / class	635 nm / 2		
Temperature range	-10 °C – +45 °C		
Weight (instrument with batteries)	0.8 kg		



\* depending on room illumination